



B.VEO ON

RECESSED LUMINAIRES

The addition of B.VEO ON to the product family now also enables store concepts without track, as the supply unit is concealed in the ceiling. Unobtrusive ceiling layouts with high flexibility in light control are the convincing result.



Light made to measure

High lumen packages and individual configuration for precisely tailored accents. Up to 5000 lumens



Best light colors & lighting effect

Individual radiant characteristics create tension in the room



Calm ceiling image

Small spotlight head, discreet ceiling crown





Intelligent light

Smart lighting management optionally with control cable or wireless



Quick assembly

Can be integrated into suspended ceilings, alignment by simply rotating and swiveling



B.VEO ONwww.oktalite.com/bveo-r

Luminaire type	Recessed luminaires
Application areas	Accent lighting
Range of action	Can be rotated through 355° and swiveled through 90
Fastening	Spring fastening (angle fastening)
Ceiling thickness	1-25 mm
Ceiling cut-out	130 mm, 155 mm
Lighting technology	LED, LED IQ DALI, LED IQ BLE
Beam angel	Spot, Medium Flood, Flood, Wide Flood, Very Wide Flood
LED luminous flux class	1500 lm - 5000 lm
Light colour CRI 80	2700 K, 3000 K, 3500 K, 4000 K
Light colour CRI 90	3100 K - Brilliant Colour, 3200 K - Efficient White, 4000 K - Efficient Cool
Light colour Food	2700 K - Brilliant Food, Meat, Meat + Fish
Supply unit	Integrated driver
Luminaire colour	RAL 9005 jet black RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
Weight	approx. 1.1 kg
Test mark	